



CHASE Construction Products
TAPECOAT / ROYSTON
PRODUCT DATA

TC ENVIROMASTIC®

A Specially Formulated
Petrolatum Wax Based
Coating Paste for Filling
Irregular Contours, Voids and
Structural Gaps

Capabilities:
Surface tolerant (wet or sweating pipe)
Corrosion Inhibiting Coating
Operational Temperature Range
Ambient to 300 °F (149 °C)

BASIC USE

TC Enviromastic is a versatile petrolatum wax paste formulation that offers a highly effective way to apply a protective coating to areas that need a filler, surface bridge or offer restrictive application access. TC Enviromastic is used to fill gaps, voids, and confined spaces such as a filler for the area between a tank chime base and concrete ring wall of a holding tank.

SURFACE PREPARATION:

Surface should be clean. Remove loose rust and scale, dust and dirt and all other foreign material including marine growth when applicable.
Substances that would impede bond or

otherwise be detrimental to the performance of the coating must be removed prior to coating application.

Application

TC Enviromastic can be applied by hand (glove), trowel or special pumping equipment.
Application Thickness: minimum 10 mils

Technical Data

ANSI/AWWA C-217 Compliant
Color: Brown
Operation Temperature Range:
Ambient to 300 °F (149 °C)

Packaging

One gallon cans
Five gallon pails
55 gallon drums
Rotate stock yearly

Additional EnviroCoat Products

TC Envirotape-Wax based tape
TC Color Coat-Color Wax based tape
TC Enviroprime-Wax based primer
TC Enviro Putty-Wax based filler putty
TC-Flangecoat-Flange filler
R Module-Wax based mat coating module

Additional Technical Data and Application Specifications are available from:

SCHRADER CO. SALES, LLC
425-377-1550 info@schraderco.com

THE TAPECOAT COMPANY

P.O. Box 631, Evanston, Illinois 60204-0631, USA
1527 Lyons Street, Evanston, Illinois 60201, USA
Telephone: (847) 866-8500 (800) 758-6041
Fax: (847) 866-8596 (800) 332-8273
www.tapecoat.com

An ISO 9001- 2000 Company Jkr11/08

WARRANTY: This product has been designed for use by persons having practical skill and experience in the application of industrial coatings. Before using, user shall determine the suitability of this product for his intended use. Since seller has no control over the specific application of this product, seller's sole warranty with respect to such product is that it is of merchantable quality and meets the quality control standards of The Tapecoat Company. Seller makes no other warranty, express or implied, and seller disclaims all warranties except as set forth herein. Seller shall not be liable under any circumstances for consequential or incidental damages. Seller's liability for breach of warranty hereunder is limited to the purchase quantity of the seller's product proved to be defective.